

CONTACT & SHIPPING INFORMATION:

Name _____

Company _____

Street _____

City _____ State _____ Zip _____

Phone _____ Email _____

Qty		U.S. PRICE	INT'L PRICE
	DIALaPRESS Includes pressing station, interchangeable tips, deck extension. Ships with service guide and tote bag.	\$325	\$345
	TouchRail Measurement information must be submitted before order can be fulfilled. Call for current wholesale pricing: (814) 883-7213		
	TouchRail One Octave Demonstrator A reduced length TouchRail, spanning a single octave. Powerful in-home presentation tool lets the customer feel the benefit of reduced touch weight instantly. Packed in a durable plastic tube.	\$35	\$45
	TouchRail Brochure 3 panel color brochure compliments any TouchRail presentation. Pack of 10.	\$15	\$25
	String Coupler Assortment Tin Each tin contains 50 standard width couplers and 50 extended width couplers. Versatile supply for all PitchLock applications.	\$45	\$55
	TouchScale Adjustable key lead calibration tool. Comes with 3 touch charts and instructions	\$35	\$45
	Felt key plugs - large 1/2" diameter Price per foot	\$6	\$8
	Felt key plugs—small 3/8" diameter Price per foot	\$6	\$8
	Crown Voicing Tool Kit 3 hardener bottles, flex voicing tool	\$45	\$55

ORDER TOTAL		
--------------------	--	--

(no additional shipping charges)

Please circle payment type: Visa MasterCard Amex Check enclosed

_____ Exp.Date: _____

Name on Card: _____ Signature: _____

TouchRail orders: In a padded envelope, return template, fasteners, this information sheet and payment to:

PitchLock, Inc. 1177 Dorum Avenue State College, PA 16801

Move the original piano stop rail to a flat surface such as a table or bench top. Place a strip of **matte finish, clear adhesive tape** (Scotch brand Magic tape recommended) across the entire length of the stop rail top surface. Retain a hand length of excess tape at each end.

Record the Stop Rail Dimensions

- With a pencil, trace the left and right outer edges of the stop rail onto the tape.
 - Carefully measure this left-right length of the stop rail with a tape measure and record this very important measurement at the far left end of the template and at the bottom of this measurement sheet.
 - Trace the circle of each fastener hole. Avoid breaking the tape surface.
- Most stop rails are fastened to the key frame by wood screws at the ends and hex or disc nuts in the middle. Tape a sample of each fastener type onto the right end of the template. The samples will be returned with your completed order.

Record the Key Locations

- Raise the stop rail lower nuts so that fastener posts do not punch through the tape template. With the stop rail back in the piano, trace a single line between each key onto the tape. These marks should accurately reflect the spacing and angles of the keys as they pass beneath the stop rail. Don't forget the outer edges of each section.
- Write the letter name of the first and last key at their location on the template.
- Place a second layer of **clear** tape over the first layer to protect your marks.
- Carefully remove the two layers of tape from the stop rail and loosely wrap the tape around two widely spaced fingers, making a loop. The template is ready to be mailed. Please use a sturdy, padded envelope and/or wrap the template in a paper towel

Piano Brand _____ Model _____

Serial Number _____ Stop Rail length _____

Are stop rail ends fastened with wood screws or disc nuts?

Is stop rail located in front or on top of key buttons? (note: If stop rail is on top of key buttons, TouchRail performance will be limited. Look for this on some Baldwin and Bosendorfer actions.)

Desired touch reduction range (if known) in grams _____

call (814) 883-7213 or visit www.pitchlock.com

